

## One way vision eco uv

- UV printable
- Indoor & outdoor window ads.
- Removable glue
- Laminated OPP film (Additional Liner)

### MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC
<b>PVC</b>		
Type	/	Calendered monomeric soft PVC film
Thickness	/	180±10um/7mil
Color	/	Ceramic Clear
Back	/	Black
Shrinkage	/	≤0.6%
Surface Tension	/	≥30dn/cm
Opacity	/	>99%
Holes No.	/	Average 130/sq in
Hole Diameter	/	1.6mm
Distance Between Holes	/	2.4mm
Hole Space	/	41%
<b>Adhesive</b>		
Type	/	Clear solvent based removable pressure sensitive glue
Weight(g/m²)	/	30±2
Adhesion Temperature	/	15°C~40°C
Peeling Force	GB2792-81 China National Standard	≥4.5N/25mm 20min
Initial Adhesion- Ball Tack	GB4852-84	≥5# Steel Ball
Holding Power	GB4854-84	≥800min
Removable Durability	/	One year cleanly removable glue on clean glass surface at temperature of 23~25°C and RH of 50~60%
<b>Liner</b>		
Type	/	Laminated OPP film (Additional Liner)
Color	/	White
Weight	/	90g±5g/m² 2.6oz/sq.yd
Release Force	/	0.2±0.1N/25mm
Available Size	/	36"/42"/50"/54"/60" 50m

### INK PRINTABILITY

Solvent	Eco Solvent	UV	Latex
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<b>Screen Printing</b>	<b>Dye Sublimation Transfer</b>	<b>Dye Sublimation Direct</b>	<b>Water based</b>

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty