

One Way vision plus

One way vision plus is a perforated pressure sensitive window film designed for short to mid-term applications so as events. This product offers 20%, 30%, 40% or 50% open area. It is perfect for those who would like to unite quality and competitiveness.

APPLICATIONS

- shop windows
- building wraps
- rear or side windows of busses and cars
- all applications up to 12 months

ADVANTAGES

- printable with solvent, ecosolvent, UV curable and latex inks
- 12 months durability warranty if applied under mid European conditions
- removability up to 1 year under normal conditions (6 months without residue)
- calendared vinyl features great dimensional stability
- special liner finish enables an easy handling when applying on the window
- semi-permanent, clear adhesive offers good removability
- designed to be combined with the over laminate Coverfilm one way vision or Coverfilm Antigrafitti |





Superior Signage Materials

Maegis B.V.

Midzomerweg 51

7532 SW Enschede

Tel: +31 (0)53 - 460 90 50

Fax: +31 (0)53 - 460 90 51

E mail: info@maegis.nl / info@maegis.de

Website: www.maegis.nl / www.maegis.de

One Way vision plus

MATERIAL

- perforated vinyl film
 - 145 micron
 - self adhesive
 - printable white front side
 - black reverse side for maximum contrast
- removable, semi-permanent clear adhesive
- excellent dimensional stability

LINER

- special liner finish
 - 135 g/m²

OPEN AREA/ PRINTABLE AREA

- open area: 20%, 30%, 40%, 50%
- printable area: 80%, 70%, 60%, 50%

APPROVALS

German TUV ~ D 5453, ~ D 5307 and
~ D 5452

PRINTING METHOD

- digital
 - solvent, eco-solvent
 - UV curable inks
 - latex inks
- screen printing

FLAMMABILITY

M1 and B1 certified

HUMIDITY AND SOLVENT RESISTANCE good

APPLICATION TEMPERATURE +10°C to
+30°C (+50°F to +86°F)

SERVICE RANGE TEMPERATURE -17°C
to +50°C (+0°F to +122°F)

SHELF LIFE

1 year, stored at +15 to +20° C (+59 to
+68° F) and relative humidity between 45% and
65%.

DURABILITY

Up to 1 year in mid European conditions. Clean
removal within 6 months. Tack may increase
over time. Not to be applied on: fresh paint or
ink, polycarbonate, certain PVC (no exhaustive
list). For critical substrates, please test prior to
application.

APPLICATION

Prevent from contact with solvent or
ammonia based cleaner. Clean window with
soap and water. Rinse and dry glass after
cleaning. ALWAYS clean and dry glass prior
to application. Please respect our application
instructions.